DELTA

see what Delta can do℠

# KITCHEN
## CATÁLOGO 2025



AKABA

COD-07072025

# YOUR KITCHEN COPILOT



### Touch$_2$O® with Touchless™ Technology

Delta® Touch$_2$O® with Touchless™ faucets make multi-tasking in the kitchen easy: simply place your hand near the faucet, tap the faucet surface, or use standard handle activation to start and stop the flow of water.



### VoiceIQ® Technology

Delta® VoiceIQ® Technology pairs with Amazon® Alexa® and Google® Assistant-enabled devices to turn the faucet on and off, warm the water, dispense a metered amount, or fill custom containers with hands-free voice activation.



### Touch$_2$O® Technology

Tap it on. Tap it off. Delta® Touch$_2$O® Technology makes kitchen tasks easy: simply tap anywhere on the spout or handle with your wrist or forearm to start and stop the flow of water.

| | | |
|---|---|---|
| No suffix | — | Chrome Finish |
| A | — | Handle Accent |
| AC | — | Alternating Current (Electronic Faucets for Hard Wire Installation) |
| ADA | — | Americans with Disabilities Act |
| ADAAG | — | Americans with Disabilities Act Accessibility Guidelines |
| AR | — | Arctic® Stainless Finish |
| AR-PR | — | Lumicoat® Arctic® Stainless Finish |
| BG | — | Polybag Packaging |
| BL | — | Matte Black Finish |
| BN | — | Brushed Nickel |
| BX | — | Single Box Model |
| BXT | — | Single Box Model, Thin Wall Mounting Kit Included |
| C | — | Cross Handle |
| CB | — | Chrome and Brilliance® Polished Brass Split Finish |
| CE | — | Cold Expansion Fitting |
| CER | — | Ceramic Cartridge |
| CH | — | Chrome Finish |
| CL | — | Clear |
| CS | — | Chrome and Matte Black Split Finish |
| CWT | — | Copper Water Tube |
| CZ | — | Champagne Bronze™ Finish |
| CZ-PR | — | Lumicoat® Champagne Bronze™ Finish |
| DST | — | DIAMOND™ Seal Technology |
| FL | — | Floor Mount |
| GB | — | Brushed Gold Finish |
| GPM | — | Gallons Per Minute (US Flow Rate) |
| GS | — | Champagne Bronze™ and Porcelain Split Finish |
| GZ | — | Matte Black and Champagne Bronze™ Split Finish |
| H | — | Handle Kit |
| HA | — | High Arc |
| H2O | — | $H_2O$kinetic® Technology |
| H2OT | — | $H_2O$kinetic® Technology |
| HDF | — | Heavy Duty Faucet |
| HF | — | High Flow |
| HGM | — | .5 Gallon per Minute Flow Rate |
| IPS | — | Iron Pipe Size |
| IP | — | IPS - Inlets / Outlets |
| kPa | — | Kilopascals (Metric Unit of Pressure) |
| KS | — | Black Stainless Finish |
| KS-PR | — | Lumicoat® Black Stainless Finish |
| L | — | Lever Handle |
| LF | — | Lead Legislation Compliant |
| LHD | — | Less Shower Head |
| LHP | — | Less Handle Program |
| L/min | — | Liters Per Minute (Metric Flow Rate) |
| LPU | — | Less Pop-Up Drain |
| LTS | — | Long Tub Spout |
| MBS | — | Mini-Bulk |
| MF | — | PEX Cold Expansion Connections |
| MPU | — | Metal Pop-Up Drain |
| NPSM | — | National Pipe Thread Straight Mechanical |
| NPT | — | National Pipe Thread Tapered |
| OB | — | Oil Rubbed Bronze Finish |
| PB | — | Brilliance® Polished Brass Finish |
| PD | — | Pull-Down Diverter Tub Spout |
| PFS | — | Prefabricated Shower |
| PFT | — | Prefabricated Tub and Shower |
| PK | — | Clamshell Packaging |
| PN | — | Polished Nickel Finish |
| PN-PR | — | Lumicoat® Polished Nickel Finish |
| PP | — | Project-Pack |
| PPU | — | Plastic Pop-Up Drain |
| PR | — | Lumicoat® Chrome Finish |
| PS | — | Peened Stainless Steel |
| PSI | — | Pounds Per Square Inch (US Unit of Pressure) |
| PX | — | Pex Crimp Connections |
| RB | — | Venetian Bronze® Finish |
| RP | — | Repair Part |
| SD | — | Soap or Lotion Dispenser |
| SH | — | Side Handle |
| SM | — | Brilliance® Stainless and Matte Black Split Finish |
| SN | — | Satin Nickel |
| SOS | — | Slip-on Spout for 1/2"– C.W.T. |
| SP | — | SpotShield® Stainless |
| SS | — | Brilliance® Stainless Finish |
| TGM | — | .35 Gallons Per Minute Flow Rate |
| TL | — | Touch$_2$O® with Touchless™ Technology |
| TLV | — | Touch$_2$O® with Touchless™ Technology + VoiceIQ® Technology |
| TP | — | Tract-Pack |
| TV | — | Touch$_2$O® Technology + VoiceIQ® Technology |
| UN | — | Universal Connection on Inlets/Outlets |
| WE | — | Water-Efficient |
| WC | — | White and Chrome Finish |
| WF | — | With Fittings—1/2" IPS Adapters |
| WH | — | White Finish or Trim |
| WL | — | Wall Mount |
| WS | — | With Stops |
| XX | — | Touch$_2$O® Solenoid Assembly for Organic Finishes |

**ADA** Products displaying this nationally recognized symbol are accessible to and usable by physically challenged persons and meet all the requirements of ICC/ANSI A117.1 and ADAAG for an operable part.

U = Universal Showering

FP = Focus Product

TE = Trade Exclusive

TOUCH$_2$O® TECHNOLOGY = Touch$_2$O® Technology

TOUCH$_2$O® WITH TOUCHLESS™ TECHNOLOGY = Touch$_2$O® with Touchless™ Technology

= VoiceIQ® Voice Activation

WaterSense® Labeled Product
Lavatory Faucets: Flow Rate of 1.2 gpm or 1.0 gpm as marked versus Industry Standard ASME A112.18.1/CSA B125.1 of 2.2 gpm.

Shower Heads and Hand Showers: Flow Rate of 1.5 to 2.0 gpm versus Industry Standard ASME A112.18.1/CSA B125.1 of 2.5 gpm.

Water-Efficient Product
Kitchen Faucets: Flow Rate of 1.8 gpm or 1.5 gpm versus Industry Standard ASME A112.18.1/CSA B125.1 of 2.2 gpm.

Lavatory Faucets: Flow Rate of 1.2 gpm or lower versus Industry Standard ASME A112.18.1/CSA B125.1 of 2.2 gpm.

Shower Heads and Hand Showers: Flow Rate of 1.5 to 2.0 gpm versus Industry Standard ASME A112.18.1/CSA B125.1 of 2.5 gpm.



## *Trade Exclusive Collections*

*Delta Faucet Company is committed to Trade advocacy and driving demand for our Trade customers. The Delta® Brand has invested in five Trade Exclusive (TE) collections, available only to Delta Trade customers' brick-and mortar locations and their authorized online stores.*

NEW!



**Broderick®**
***Single Handle Spring Spout Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9690TL-DST | 1.8 gpm |
| 9690TL-AR-DST | 1.8 gpm |
| 9690TL-BL-DST | 1.8 gpm |
| 9690TL-CZ-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Polished Nickel Finish Available Q4 2025**

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation, for 3 hole order RP100845
- 9 5/8" long, 20 3/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

NEW!



**Broderick®**
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9190TL-DST | 1.8 gpm |
| 9190TL-AR-DST | 1.8 gpm |
| 9190TL-BL-DST | 1.8 gpm |
| 9190TL-CZ-DST | 1.8 gpm |
| 9190TL-KS-DST | 1.8 gpm |
| 9190TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Polished Nickel Finish Available Q4 2025**

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation, for 3 hole order RP100845
- 9 5/8" long, 16 1/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings



**Broderick®**
***Single Handle Spring Spout Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9690T-DST | 1.8 gpm |
| 9690T-AR-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 9 5/8" long, 20 3/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



**Broderick®**
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9190T-DST | 1.8 gpm |
| 9190T-AR-DST | 1.8 gpm |
| 9190T-BL-DST | 1.8 gpm |
| 9190T-CZ-DST | 1.8 gpm |
| 9190T-KS-DST | 1.8 gpm |
| 9190T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 9 5/8" long, 16 1/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



### Broderick®
### *Two Handle Bridge Pull-Down Kitchen Faucet*

| Model | Flow |
|---|---|
| 2390L-DST | 1.8 gpm |
| 2390L-AR-DST | 1.8 gpm |
| 2390L-BL-DST | 1.8 gpm |
| 2390L-CZ-DST | 1.8 gpm |
| 2390L-KS-DST | 1.8 gpm |
| 2390L-RB-DST | 1.8 gpm |

**New Polished Nickel Finish Available Q4 2025**

**Features ShieldSpray® Technology**

- 3-hole 8" installation
- 9 5/8" long, 15 7/8" high
- Hot/cold indicators
- 3" max. deck thickness
- 30" min. Innoflex supply lines
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- DIAMOND™ Valve
- MagnaTite® docking

NEW!



### Broderick®
### *Single Handle Spring Spout Pull-Down Kitchen Faucet*

| Model | Flow |
|---|---|
| 9690-DST | 1.8 gpm |
| 9690-AR-DST | 1.8 gpm |
| 9690-BL-DST | 1.8 gpm |
| 9690-CZ-DST | 1.8 gpm |

**New Matte Black and Champagne Bronze™ Finishes Available Now**

**New Polished Nickel Finish Available Q4 2025**

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 9 5/8" long, 20 3/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



### Broderick®
### *Single Handle Pull-Down Kitchen Faucet*

| Model | Flow |
|---|---|
| 9190-DST | 1.8 gpm |
| 9190-AR-DST | 1.8 gpm |
| 9190-BL-DST | 1.8 gpm |
| 9190-CZ-DST | 1.8 gpm |
| 9190-KS-DST | 1.8 gpm |
| 9190-RB-DST | 1.8 gpm |

**New Polished Nickel Finish Available Q4 2025**

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 9 5/8" long, 15 5/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



### Broderick®
### *Single Handle Pull-Down Bar / Prep Faucet*

| Model | Flow |
|---|---|
| 9990TL-DST | 1.8 gpm |
| 9990TL-AR-DST | 1.8 gpm |
| 9990TL-BL-DST | 1.8 gpm |
| 9990TL-CZ-DST | 1.8 gpm |
| 9990TL-KS-DST | 1.8 gpm |
| 9990TL-RB-DST | 1.8 gpm |

TOUCH$_2$O®
WITH **TOUCHLESS**™
TECHNOLOGY

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP100845
- 6 5/8" long, 15 1/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch$_2$O® only settings

See page 3 for icon definitions.



### Broderick®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9990T-DST | 1.8 gpm |
| 9990T-AR-DST | 1.8 gpm |
| 9990T-BL-DST | 1.8 gpm |
| 9990T-CZ-DST | 1.8 gpm |
| 9990T-KS-DST | 1.8 gpm |
| 9990T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 6 5/8" long, 15 1/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated 6 (AA) or 6(C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



### Broderick®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9990-DST | 1.8 gpm |
| 9990-AR-DST | 1.8 gpm |
| 9990-BL-DST | 1.8 gpm |
| 9990-CZ-DST | 1.8 gpm |
| 9990-KS-DST | 1.8 gpm |
| 9990-RB-DST | 1.8 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 6 5/8" long, 14 5/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



### Broderick®
***Single Handle Bar Faucet***

| Model | Flow |
|---|---|
| 1990LFC | 1.5 gpm |
| 1990LFC-AR | 1.5 gpm |
| 1990LFC-BL | 1.5 gpm |
| 1990LFC-CZ | 1.5 gpm |
| 1990LFC-KS | 1.5 gpm |
| 1990LFC-RB | 1.5 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 4" installation; for 3-hole, order RP100844 escutcheon
- 7 1/16" long, 12 1/4" high
- 2 1/2" max. deck thickness

NEW!



### Broderick®
***Wall Mount Pot Filler***

| Model | Flow |
|---|---|
| 1190LFL | 4.0 gpm |
| 1190LFL-AR | 4.0 gpm |
| 1190LFL-BL | 4.0 gpm |
| 1190LFL-CZ | 4.0 gpm |
| 1190LFL-KS | 4.0 gpm |
| 1190LFL-RB | 4.0 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1-hole installation
- 24" long, 9 1/4" high
- Two handle wall mount
- Cold water only
- Dual shut-off and swing joints
- 24" reach

NEW!



### Broderick®
***Metal Soap / Lotion Dispenser***

| Model |
|---|
| RP100632 |
| RP100632AR |
| RP100632BL |
| RP100632CZ |
| RP100632KS |
| RP100632RB |

**New Polished Nickel Finish Available Q4 2025**

- 13-ounce bottle
- Refillable from above the deck
- 3" max. deck thickness

**See page 3 for icon definitions.**





## *Trade Exclusive Collections*

*Delta Faucet Company is committed to Trade advocacy and driving demand for our Trade customers. The Delta® Brand has invested in five Trade Exclusive (TE) collections, available only to Delta Trade customers' brick-and mortar locations and their authorized online stores.*



**Coranto®**
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9179TL-DST | 1.8 gpm |
| 9179TL-AR-DST | 1.8 gpm |
| 9179TL-BL-DST | 1.8 gpm |
| 9179TL-CZ-DST | 1.8 gpm |
| 9179TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 16 1/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- Battery operated - (AA) or 6 (C)
- TempSense® light indicates water temp.
- ShieldSpray® Technology powers off the mess without making a mess
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings



**Coranto®**
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9179T-DST | 1.8 gpm |
| 9179T-AR-DST | 1.8 gpm |
| 9179T-BL-DST | 1.8 gpm |
| 9179T-CZ-DST | 1.8 gpm |
| 9179T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 16 1/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- Battery operated 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- ShieldSpray® Technology powers off the mess without making a mess
- MagnaTite® docking



**Coranto®**
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9179-DST | 1.8 gpm |
| 9179-AR-DST | 1.8 gpm |
| 9179-BL-DST | 1.8 gpm |
| 9179-CZ-DST | 1.8 gpm |
| 9179-RB-DST | 1.8 gpm |

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 15 13/16" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- ShieldSpray® Technology powers off the mess without making a mess
- MagnaTite® docking

**See page 3 for icon definitions.**



**Coranto®**
***Single Handle Pull-Down Bar/Prep Faucet***

| Model | Flow |
|---|---|
| 9979TL-DST | 1.8 gpm |
| 9979TL-AR-DST | 1.8 gpm |
| 9979TL-BL-DST | 1.8 gpm |
| 9979TL-CZ-DST | 1.8 gpm |
| 9979TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

- 1 or 3-hole 8" installation, for 3 hole order RP47274 escutcheon
- 6 7/8" long, 14 7/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- Battery operated 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings



**Coranto®**
***Single Handle Pull-Down Bar/Prep Faucet***

| Model | Flow |
|---|---|
| 9979T-DST | 1.8 gpm |
| 9979T-AR-DST | 1.8 gpm |
| 9979T-BL-DST | 1.8 gpm |
| 9979T-CZ-DST | 1.8 gpm |
| 9979T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation, for 3-hole, order RP47274 escutcheon
- 6 7/8" long, 14 7/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- Battery operated 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- MagnaTite® docking



**Coranto®**
***Single Handle Pull-Down Bar/Prep Faucet***

| Model | Flow |
|---|---|
| 9979-DST | 1.8 gpm |
| 9979-AR-DST | 1.8 gpm |
| 9979-BL-DST | 1.8 gpm |
| 9979-CZ-DST | 1.8 gpm |
| 9979-RB-DST | 1.8 gpm |

- 1 or 3-hole 8" installation, for 3-hole, order RP47274 escutcheon
- 6 7/8" long, 14 7/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



See page 3 for icon definitions.





## Pull-down Price Continuum

Broderick®



Cassidy®



Stryke®



Trinsic®



Emmeline®



Theodora®



Monrovia®



Renaldi™



Antoni®



Leland®



Coranto®



Essa®



Lenta®



Westville®



## Pull-out Price Continuum

Cassidy®



Signature™



Trinsic®



Linden®



Linden®



Collins®



Foundations®



Almari™



Daneri™



NEW!



### Trinsic®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9159TLV-DST | 1.8 gpm |
| 9159TLV-AR-DST | 1.8 gpm |
| 9159TLV-BL-DST | 1.8 gpm |
| 9159TLV-CZ-DST | 1.8 gpm |
| 9159TLV-KS-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

***VoiceIQ® Hands-Free Voice Activation***

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP64070 escutcheon
- 9 1/2" long, 15 11/16" high
- Finished red/blue indicator
- Spout swivels 360°
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- Battery back-up - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings
- Includes 9 volt power supply
- Requires outlet not operated on a switch
- VoiceIQ® Technology for hands-free voice activation
- Pairs with Amazon® Alexa® and Google® Assistant-enabled devices
- Metered and Custom dispensing options
- Includes feature to warm the water
- Includes “handwash mode” feature

NEW!



### Stryke®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9176TLV-PR-DST | 1.8 gpm |
| 9176TLV-AR-PR-DST | 1.8 gpm |
| 9176TLV-BL-DST | 1.8 gpm |
| 9176TLV-CZ-PR-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

***VoiceIQ® Hands-Free Voice Activation***

**New Matte Black / Lumicoat® Champagne Bronze™ Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP100190
- 9" long, 17 1/4" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery back-up - 6 (AA) or 6 ©
- TempSense® light indicates water temp.
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings
- Includes 9 volt power supply
- Requires outlet not operated on a switch
- VoiceIQ® Technology for hands-free voice activation
- Pairs with Amazon Alexa® and google Assistant-enabled devices
- Metered and custom dispensing options
- Includes feature to warm the water
- Includes "handwash mode" feature
- PR - Lumicoat Finishes, guaranteed to resist mineral buildup and hard water stains



### Leland®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9178TLV-DST | 1.8 gpm |
| 9178TLV-AR-DST | 1.8 gpm |
| 9178TLV-BL-DST | 1.8 gpm |
| 9178TLV-CZ-DST | 1.8 gpm |
| 9178TLV-RB-DST | 1.8 gpm |
| 9178TLV-SP-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

***VoiceIQ® Hands-Free Voice Activation***

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 13/64" long, 14 7/8" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- TempSense® light indicates water temp
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- SP - SpotShield® finish resists spots, prints and stains; also includes antimicrobial protection of the finish
- DIAMOND™ Valve
- MagnaTite® docking
- Battery back-up - 6 (AA) or 6 (C)
- Toggle between Touchless and Touch2O® only settings
- Includes 9 volt power supply
- Requires outlet not operated on a switch
- VoiceIQ® Technology for hands-free voice activation
- Pairs with Amazon® Alexa® and Google® Assistant-enabled devices
- Metered and Custom dispensing options
- Includes feature to warm the water
- Includes “handwash mode” feature

**See page 3 for icon definitions.**

NEW!



## Essa®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9113TLV-DST | 1.8 gpm |
| 9113TLV-AR-DST | 1.8 gpm |
| 9113TLV-BL-DST | 1.8 gpm |
| 9113TLV-CZ-DST | 1.8 gpm |
| 9113TLV-RB-DST | 1.8 gpm |

TOUCH$_2$O® WITH TOUCHLESS™ TECHNOLOGY

***VoiceIQ® Hands-Free Voice Activation***

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 16" high
- Red/Blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery back-up - 6 (AA) or 6 ©
- TempSense® light indicates water temp.
- MagnaTite® docking
- Toggle between Touchless and Touch$_2$O® only settings
- Includes 9 volt power supply
- Requires outlet not operated on a switch
- VoiceIQ® Technology for hands-free voice activation
- Pairs with Amazon Alexa® and google Assistant-enabled devices
- Metered and custom dispensing options
- Includes feature to warm the water
- Includes "handwash mode" feature



## Stryke®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9176TV-PR-DST | 1.8 gpm |
| 9176TV-AR-PR-DST | 1.8 gpm |
| 9176TV-BL-DST | 1.8 gpm |
| 9176TV-CZ-PR-DST | 1.8 gpm |

TOUCH$_2$O® TECHNOLOGY

***VoiceIQ® Hands-Free Voice Activation***

- 1 or 3-hole 8" installation; for 3-hole, order RP100190 Escutcheon
- 9" long, 17 1/4" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- Battery back-up - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- MagnaTite® docking
- Includes 9 volt power supply
- Requires outlet not operated on a switch
- VoiceIQ® Technology for hands-free voice activation
- Pairs with Amazon Alexa®- and Google Assistant-enabled devices
- Metered and custom dispensing options
- Includes feature to warm the water
- Includes “handwash mode” feature
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains



## Trinsic®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9159TV-DST | 1.8 gpm |
| 9159TV-AR-DST | 1.8 gpm |
| 9159TV-BL-DST | 1.8 gpm |
| 9159TV-CZ-DST | 1.8 gpm |
| 9159TV-KS-DST | 1.8 gpm |

TOUCH$_2$O® TECHNOLOGY

***VoiceIQ® Hands-Free Voice Activation***

- 1 or 3-hole 8" installation; for 3-hole, order RP64070 escutcheon
- 9 1/2" long, 15 11/16" high
- Red/blue indicators
- Spout swivels 360°
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- Battery back-up - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- MagnaTite® docking
- Includes 9 volt power supply
- Requires outlet not operated on a switch
- VoiceIQ® Technology for hands-free voice activation
- Pairs with Amazon® Alexa®- and Google® Assistant-enabled devices
- Metered and custom dispensing options
- Includes feature to warm the water
- Includes “handwash mode” feature



See page 3 for icon definitions.



## Leland®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9178TV-DST | 1.8 gpm |
| 9178TV-AR-DST | 1.8 gpm |
| 9178TV-BL-DST | 1.8 gpm |
| 9178TV-CZ-DST | 1.8 gpm |
| 9178TV-RB-DST | 1.8 gpm |
| 9178TV-SP-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

***VoiceIQ® Hands-Free Voice Activation***

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 13/64" long, 14 7/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- Battery back-up - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- MagnaTite® docking
- ShieldSpray® Technology powers off the mess without making a mess
- SP - SpotShield® finish resists spots, prints and stains with antimicrobial protection of the finish
- Includes 9 volt power supply
- Requires outlet not operated on a switch
- VoiceIQ® Technology for hands-free voice activation
- Pairs with Amazon® Alexa®- and Google® Assistant-enabled devices
- Metered and custom dispensing options
- Includes feature to warm the water
- Includes "handwash mode" feature



## Essa®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9113TV-DST | 1.8 gpm |
| 9113TV-AR-DST | 1.8 gpm |
| 9113TV-BL-DST | 1.8 gpm |
| 9113TV-CZ-DST | 1.8 gpm |
| 9113TV-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

***VoiceIQ® Hands-Free Voice Activation***

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 16" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- Battery back-up - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- MagnaTite® docking
- Includes 9 volt power supply
- Requires outlet not operated on a switch
- VoiceIQ® Technology for hands-free voice activation
- Pairs with Amazon® Alexa®- and Google® Assistant-enabled devices
- Metered and custom dispensing options
- Includes feature to warm the water
- Includes "handwash mode" feature

**NEW!**



## Broderick®
***Single Handle Spring Spout Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9690TL-DST | 1.8 gpm |
| 9690TL-AR-DST | 1.8 gpm |
| 9690TL-BL-DST | 1.8 gpm |
| 9690TL-CZ-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Polished Nickel Finish Available Q4 2025**

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation, for 3 hole order RP100845
- 9 5/8" long, 19 15/16" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch$_2$O® only settings

**See page 3 for icon definitions.**

NEW!



### Trinsic®
### *Single Handle Spring Spout Pull-Down Kitchen Faucet*

| Model | Flow |
|---|---|
| 9659TL-DST | 1.8 gpm |
| 9659TL-AR-DST | 1.8 gpm |
| 9659TL-BL-DST | 1.8 gpm |
| 9659TL-CZ-DST | 1.8 gpm |
| 9659TL-KS-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Matte Black and Champagne Bronze™ Finishes Available**

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP64070 escutcheon
- 9 1/2" long, 20 3/8" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- 1 or 3-hole installation, for 3 hole order RP100845
- TempSense® light indicates water temp
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

NEW!



### Trinsic®
### *Single Handle Pull-Down Kitchen Faucet*

| Model | Flow |
|---|---|
| 9159TL-DST | 1.8 gpm |
| 9159TL-AR-DST | 1.8 gpm |
| 9159TL-BL-DST | 1.8 gpm |
| 9159TL-CZ-DST | 1.8 gpm |
| 9159TL-KS-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP64070 escutcheon
- 9 1/2" long, 15 11/16" high
- Finished red/blue indicator
- Spout swivels 360°
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

NEW!



### Broderick®
### *Single Handle Pull-Down Kitchen Faucet*

| Model | Flow |
|---|---|
| 9190TL-DST | 1.8 gpm |
| 9190TL-AR-DST | 1.8 gpm |
| 9190TL-BL-DST | 1.8 gpm |
| 9190TL-CZ-DST | 1.8 gpm |
| 9190TL-KS-DST | 1.8 gpm |
| 9190TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Polished Nickel Finish Available Q4 2025**

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation, for 3 hole order RP100845
- 9 5/8" long, 16 1/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings



See page 3 for icon definitions.

NEW!



### Cassidy®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9197TL-PR-DST | 1.8 gpm |
| 9197TL-AR-PR-DST | 1.8 gpm |
| 9197TL-CZ-PR-DST | 1.8 gpm |
| 9197TL-PN-PR-DST | 1.8 gpm |
| 9197TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation, for 3 hole order RP71545
- 9 3/8" long, 16" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euromotion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

---

NEW!



### Stryke®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9176TL-PR-DST | 1.8 gpm |
| 9176TL-AR-PR-DST | 1.8 gpm |
| 9176TL-BL-DST | 1.8 gpm |
| 9176TL-CZ-PR-DST | 1.8 gpm |

TOUCH2O WITH TOUCHLESS™ TECHNOLOGY

**New Matte Black / Lumicoat® Champagne Bronze™ Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP100190
- 9" long, 17 1/4" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

---

NEW!



### Emmeline®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9182TL-PR-DST | 1.8 gpm |
| 9182TL-AR-PR-DST | 1.8 gpm |
| 9182TL-BL-DST | 1.8 gpm |
| 9182TL-CZ-PR-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Lumicoat® Polished Nickel Finish Available Q4 2025**

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 17 1/16" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euromotion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

---



### Renaldi™
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9184TL-PR-DST | 1.8 gpm |
| 9184TL-AR-PR-DST | 1.8 gpm |
| 9184TL-BL-DST | 1.8 gpm |
| 9184TL-CZ-PR-DST | 1.8 gpm |
| 9184TL-PN-PR-DST | 1.8 gpm |
| 9184TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**Features ProClean™ Spray**

- 1 or 3-hole installation, for 3 hole order RP100845
- 9 5/8" long, 19 3/4" high
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- 3/8" compression fittings
- Features ProClean™ Kitchen Spray Wand to provide a powerful, wide fan spray for quick and complete cleaning
- Euromotion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

**See page 3 for icon definitions.**

NEW!



### Monrovia®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9191TL-PR-DST | 1.8 gpm |
| 9191TL-AR-PR-DST | 1.8 gpm |
| 9191TL-BL-DST | 1.8 gpm |
| 9191TL-CZ-PR-DST | 1.8 gpm |

TOUCH$_2$O WITH TOUCHLESS™ TECHNOLOGY

**New Matte Black / Lumicoat® Champagne Bronze™ Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP47274
- 9" long, 16 5/8" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking
- Toggle between Touchless and Touch$_2$O® only settings



### Leland®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9178TL-DST | 1.8 gpm |
| 9178TL-AR-DST | 1.8 gpm |
| 9178TL-BL-DST | 1.8 gpm |
| 9178TL-CZ-DST | 1.8 gpm |
| 9178TL-RB-DST | 1.8 gpm |
| 9178TL-SP-DST | 1.8 gpm |

TOUCH$_2$O® WITH TOUCHLESS™ TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 13/64" long, 14 7/8" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- SP - SpotShield® finish resists spots, prints and stains; also includes antimicrobial protection of the finish
- DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch$_2$O® only settings



### Coranto®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9179TL-DST | 1.8 gpm |
| 9179TL-AR-DST | 1.8 gpm |
| 9179TL-BL-DST | 1.8 gpm |
| 9179TL-CZ-DST | 1.8 gpm |
| 9179TL-RB-DST | 1.8 gpm |

TOUCH$_2$O® WITH TOUCHLESS™ TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 16 1/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch$_2$O® only settings

NEW!



### Essa®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9113TL-DST | 1.8 gpm |
| 9113TL-AR-DST | 1.8 gpm |
| 9113TL-BL-DST | 1.8 gpm |
| 9113TL-CZ-DST | 1.8 gpm |
| 9113TL-RB-DST | 1.8 gpm |

TOUCH$_2$O® WITH TOUCHLESS™ TECHNOLOGY

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 16" high
- Red/Blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch$_2$O® only settings



**See page 3 for icon definitions.**

NEW!



### Lenta®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 19802TLZ-DST | 1.8 gpm |
| 19802TLZ-BL-DST | 1.8 gpm |
| 19802TLZ-CZ-DST | 1.8 gpm |
| 19802TLZ-GB-DST | 1.8 gpm |
| 19802TLZ-SP-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 1/8" long, 15 3/4" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euromotion DIAMOND™ Valve
- SP - SpotShield® finish resists spots, prints and stains, also includes antimicrobial protection of the finish
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings



### Broderick®
***Single Handle Spring Spout Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9690T-DST | 1.8 gpm |
| 9690T-AR-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 9 5/8" long, 20 3/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



### Cassidy®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9197T-PR-DST | 1.8 gpm |
| 9197T-AR-PR-DST | 1.8 gpm |
| 9197T-CZ-PR-DST | 1.8 gpm |
| 9197T-PN-PR-DST | 1.8 gpm |
| 9197T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation, for 3-hole, order RP71545 escutcheon
- 9 3/8" long, 16" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32""minimum InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- ShieldSpray® Technology powers off the mess without making a mess
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking



### Broderick®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9190T-DST | 1.8 gpm |
| 9190T-AR-DST | 1.8 gpm |
| 9190T-BL-DST | 1.8 gpm |
| 9190T-CZ-DST | 1.8 gpm |
| 9190T-KS-DST | 1.8 gpm |
| 9190T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 9 5/8" long, 16 1/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



### Trinsic®
***Single Handle Spring Spout Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9659T-DST | 1.8 gpm |
| 9659T-AR-DST | 1.8 gpm |
| 9659T-KS-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP64070 escutcheon
- 9 1/2" long, 20 3/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

**See page 3 for icon definitions.**



### Stryke®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9176T-PR-DST | 1.8 gpm |
| 9176T-AR-PR-DST | 1.8 gpm |
| 9176T-BL-DST | 1.8 gpm |
| 9176T-CZ-PR-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP100190 escutcheon
- 9" long, 17 1/4" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



### Trinsic®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9159T-DST | 1.8 gpm |
| 9159T-AR-DST | 1.8 gpm |
| 9159T-BL-DST | 1.8 gpm |
| 9159T-CZ-DST | 1.8 gpm |
| 9159T-KS-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP64070 escutcheon
- 9 1/2" long, 15 11/16" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



### Emmeline®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9182T-PR-DST | 1.8 gpm |
| 9182T-AR-PR-DST | 1.8 gpm |
| 9182T-BL-DST | 1.8 gpm |
| 9182T-CZ-PR-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation, for 3-hole, order RP47274 escutcheon
- 9 3/8" long, 17 1/16" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- ShieldSpray® Technology powers off the mess without making a mess
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking



### Monrovia®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9191T-PR-DST | 1.8 gpm |
| 9191T-AR-PR-DST | 1.8 gpm |
| 9191T-BL-DST | 1.8 gpm |
| 9191T-CZ-PR-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP47274
- 9" long, 16 5/8" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking



### Leland®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9178T-DST | 1.8 gpm |
| 9178T-AR-DST | 1.8 gpm |
| 9178T-BL-DST | 1.8 gpm |
| 9178T-CZ-DST | 1.8 gpm |
| 9178T-RB-DST | 1.8 gpm |
| 9178T-SP-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 13/64" long, 14 7/8" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- SP - SpotShield® finish resists spots, prints and stains; also includes antimicrobial protection of the finish
- DIAMOND™ Valve
- MagnaTite® docking



See page 3 for icon definitions.



## Coranto®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9179T-DST | 1.8 gpm |
| 9179T-AR-DST | 1.8 gpm |
| 9179T-BL-DST | 1.8 gpm |
| 9179T-CZ-DST | 1.8 gpm |
| 9179T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 16 1/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- ShieldSpray® Technology powers off the mess without making a mess
- MagnaTite® docking

**NEW!**



## Lenta®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 19802TZ-DST | 1.8 gpm |
| 19802TZ-BL-DST | 1.8 gpm |
| 19802TZ-CZ-DST | 1.8 gpm |
| 19802TZ-GB-DST | 1.8 gpm |
| 19802TZ-SP-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

**Features ShieldSpray® Technology**

**New Brushed Gold Finish Available**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 1/8" long, 15 3/4" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- SP - SpotShield® finish resists spots, prints and stains, also includes antimicrobial protection of the finish
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



## Essa®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9113T-DST | 1.8 gpm |
| 9113T-AR-DST | 1.8 gpm |
| 9113T-BL-DST | 1.8 gpm |
| 9113T-CZ-DST | 1.8 gpm |
| 9113T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 16" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

**NEW!**



## Broderick®
***Two Handle Bridge Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 2390L-DST | 1.8 gpm |
| 2390L-AR-DST | 1.8 gpm |
| 2390L-BL-DST | 1.8 gpm |
| 2390L-CZ-DST | 1.8 gpm |
| 2390L-KS-DST | 1.8 gpm |
| 2390L-RB-DST | 1.8 gpm |

**Features ShieldSpray® Technology**

**New Polished Nickel Finish Available Q4 2025**

- 3 hole installation
- 9 5/8" long, 15 7/8" high
- Hot/cold indicators
- 3" max. deck thickness
- 30" min. InnoFlex® supply lines
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- DIAMOND™ Valve
- MagnaTite® docking

**See page 3 for icon definitions.**



## Renaldi™
***Two Handle Bridge Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 2384L-PR-DST | 1.8 gpm |
| 2384L-AR-PR-DST | 1.8 gpm |
| 2384L-BL-DST | 1.8 gpm |
| 2384L-CZ-PR-DST | 1.8 gpm |
| 2384L-PN-PR-DST | 1.8 gpm |
| 2384L-RB-DST | 1.8 gpm |

**Features ProClean™ Spray**

- 3 hole installation
- 9 5/8" long, 15 7/8" high
- 3" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- ProClean™ Kitchen Spray Wand to provide a powerful, wide fan spray for quick and complete cleaning
- DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking

NEW!



## Broderick®
***Single Handle Spring Spout Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9690-DST | 1.8 gpm |
| 9690-AR-DST | 1.8 gpm |
| 9690-BL-DST | 1.8 gpm |
| 9690-CZ-DST | 1.8 gpm |

**Features ShieldSpray® Technology**

**New Matte Black and Champagne Bronze™ Finishes Available**

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 9 5/8" long, 19 15/16" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



## Trinsic®
***Single Handle Spring Spout Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9659-DST | 1.8 gpm |
| 9659-AR-DST | 1.8 gpm |
| 9659-BL-DST | 1.8 gpm |
| 9659-CZ-DST | 1.8 gpm |
| 9659-KS-DST | 1.8 gpm |

**New Matte Black and Champagne Bronze™ Finishes Available**

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP64070 escutcheon
- 9 1/2" long, 19 5/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



## Broderick®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9190-DST | 1.8 gpm |
| 9190-AR-DST | 1.8 gpm |
| 9190-BL-DST | 1.8 gpm |
| 9190-CZ-DST | 1.8 gpm |
| 9190-KS-DST | 1.8 gpm |
| 9190-RB-DST | 1.8 gpm |

**Features ShieldSpray® Technology**

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 9 5/8" long, 15 5/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



See page 3 for icon definitions.



### Cassidy®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9197-PR-DST | 1.8 gpm |
| 9197-AR-PR-DST | 1.8 gpm |
| 9197-CZ-PR-DST | 1.8 gpm |
| 9197-PN-PR-DST | 1.8 gpm |
| 9197-RB-DST | 1.8 gpm |

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation, for 3-hole, order RP71545 escutcheon
- 9 3/8" long, 15 1/2" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- ShieldSpray® Technology powers off the mess without making a mess
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking

---

NEW!



### Stryke®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9176-PR-DST | 1.8 gpm |
| 9176-AR-PR-DST | 1.8 gpm |
| 9176-BL-DST | 1.8 gpm |
| 9176-CZ-PR-DST | 1.8 gpm |

**New Matte Black / Lumicoat® Champagne Bronze™ Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP100190 escutcheon
- 9" long, 16 3/4" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-Motion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking

---

NEW!



### Trinsic®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9159-DST | 1.8 gpm |
| 9159-AR-DST | 1.8 gpm |
| 9159-BL-DST | 1.8 gpm |
| 9159-CZ-DST | 1.8 gpm |
| 9159-KS-DST | 1.8 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP64070 escutcheon
- 9 1/2" long, 15 11/16" high
- Red/blue indicators
- Spout swivels 360°
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

---

NEW!



### Trinsic®
***Limited Swivel Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9159-LS-DST | 1.8 gpm |
| 9159-ARLS-DST | 1.8 gpm |
| 9159-BLLS-DST | 1.8 gpm |
| 9159-CZLS-DST | 1.8 gpm |
| 9159-KSLS-DST | 1.8 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP64070 escutcheon
- 9 1/2" long, 15 11/16" high
- Red/blue indicators
- Spout swivels 140°
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

---

**See page 3 for icon definitions.**



### Essa®
***Single Handle Spring Spout Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9613-DST | 1.8 gpm |
| 9613-AR-DST | 1.8 gpm |
| 9613-BL-DST | 1.8 gpm |
| 9613-CZ-DST | 1.8 gpm |
| 9613-RB-DST | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 5/8" long, 19 3/4" high
- Hot/Cold Indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- MagnaTite™ docking

NEW!



### Emmeline®
***Single Handle Pull-Down Kitchen Faucet***

FP

| Model | Flow |
|---|---|
| 9182-PR-DST | 1.8 gpm |
| 9182-AR-PR-DST | 1.8 gpm |
| 9182-BL-DST | 1.8 gpm |
| 9182-CZ-PR-DST | 1.8 gpm |

**Features ShieldSpray® Technology**

**New Lumicoat® Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 16 5/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- ShieldSpray® Technology powers off the mess without making a mess
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking



### Theodora®
***Single Handle Spring Spout Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 18804Z-DST | 1.8 gpm |
| 18804Z-BL-DST | 1.8 gpm |
| 18804Z-CZ-DST | 1.8 gpm |
| 18804Z-RB-DST | 1.8 gpm |
| 18804Z-SP-DST | 1.8 gpm |

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 5/8" long, 19 3/4" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- SP - SpotShield® finish resists spots, prints and staines, also includes antimicrobial protection of the finish
- Euromotion DIAMOND™ Valve
- MagnaTite™ docking

NEW!



### Monrovia®
***Single Handle Pull-Down Kitchen Faucet***

FP

| Model | Flow |
|---|---|
| 9191-PR-DST | 1.8 gpm |
| 9191-AR-PR-DST | 1.8 gpm |
| 9191-BL-DST | 1.8 gpm |
| 9191-CZ-PR-DST | 1.8 gpm |

**New Matte Black / Lumicoat® Champagne Bronze™ Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP47274
- 9" long, 16 1/8" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking



### Renaldi™
***Single Handle Pull-Down Kitchen Faucet***

FP

| Model | Flow |
|---|---|
| 9184-PR-DST | 1.8 gpm |
| 9184-AR-PR-DST | 1.8 gpm |
| 9184-BL-DST | 1.8 gpm |
| 9184-CZ-PR-DST | 1.8 gpm |
| 9184-PN-PR-DST | 1.8 gpm |
| 9184-RB-DST | 1.8 gpm |

**Features ProClean™ Spray**

- 1 or 3-hole 8" installation, for 3-hole order RP100845
- 9 5/8" long, 19 3/4" high
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- ProClean™ Kitchen Spray Wand to provide a powerful, wide fan spray for quick and complete cleaning
- Euromotion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite™ docking



### Antoni®
***Single Handle Spring Spout Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 18803-DST | 1.8 gpm |
| 18803-BL-DST | 1.8 gpm |
| 18803-CZ-DST | 1.8 gpm |
| 18803-SP-DST | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 5/8" long, 19 3/4" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



See page 3 for icon definitions.



### Leland®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 978-DST | 1.8 gpm |
| 978-AR-DST | 1.8 gpm |
| 978-BL-DST | 1.8 gpm |
| 978-BLWE-DST | 1.5 gpm |
| 978-CZ-DST | 1.8 gpm |
| 978-RB-DST | 1.8 gpm |

- 2-hole 4" installation
- 9 3/16" long, 14 1/4" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- MagnaTite® docking



### Leland®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9178-DST | 1.8 gpm |
| 9178-AR-DST | 1.8 gpm |
| 9178-BL-DST | 1.8 gpm |
| 9178-CZ-DST | 1.8 gpm |
| 9178-RB-DST | 1.8 gpm |
| 9178-SP-DST | 1.8 gpm |

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 13/64" long, 14 7/8" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- SP - SpotShield® finish resists spots, prints and stains; also includes antimicrobial protection of the finish
- DIAMOND™ Valve
- MagnaTite® docking



### Coranto®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9179-DST | 1.8 gpm |
| 9179-AR-DST | 1.8 gpm |
| 9179-BL-DST | 1.8 gpm |
| 9179-CZ-DST | 1.8 gpm |
| 9179-RB-DST | 1.8 gpm |

**Features ShieldSpray® Technology**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 16 1/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- ShieldSpray® Technology powers off the mess without making a mess
- MagnaTite® docking



### Essa®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9113-DST | 1.8 gpm |
| 9113-AR-DST | 1.8 gpm |
| 9113-BL-DST | 1.8 gpm |
| 9113-CZ-DST | 1.8 gpm |
| 9113-RB-DST | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/8" long, 15 3/4" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



### Lenta®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 19802Z-DST | 1.8 gpm |
| 19802Z-BL-DST | 1.8 gpm |
| 19802Z-CZ-DST | 1.8 gpm |
| 19802Z-GB-DST | 1.8 gpm |
| 19802Z-SP-DST | 1.8 gpm |

**Features ShieldSpray® Technology**

**New Brushed Gold Finish Available**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 1/8" long, 15 3/4" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- SP - SpotShield® finish resists spots, prints and staines, also includes antimicrobial protection of the finish
- Euromotion DIAMOND™ Valve
- MagnaTite™ docking



### Westville®
***Single Handle Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 9110-DST | 1.8 gpm |
| 9110-AR-DST | 1.8 gpm |
| 9110-BL-DST | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 3/16" long, 15 1/16" high
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

**See page 3 for icon definitions.**



### Cassidy®
***Single Handle Pull-Out Kitchen Faucet***

| Model | Flow |
|---|---|
| 4197-DST | 1.8 gpm |
| 4197-AR-DST | 1.8 gpm |
| 4197-CZ-DST | 1.8 gpm |
| 4197-PN-DST | 1.8 gpm |
| 4197-RB-DST | 1.8 gpm |

- 1 or 3-hole 8" installation; for 3-hole, order RP71545 escutcheon
- 10 1/16" long, 10 1/2" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve



### Signature™
***Single Handle Pull-Out Kitchen Faucet***

| Model | Flow |
|---|---|
| 470-DST | 1.8 gpm |
| 470-WE-DST | 1.5 gpm |
| 470-AR-DST | 1.8 gpm |
| 470-BL-DST | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9" long, 10" high
- Red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve

NEW!



### Trinsic®
***Single Handle Pull-Out Kitchen Faucet***

| Model | Flow |
|---|---|
| 4159-DST | 1.8 gpm |
| 4159-AR-DST | 1.8 gpm |
| 4159-BL-DST | 1.8 gpm |
| 4159-KS-DST | 1.8 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP64070 escutcheon
- 9 1/4" long, 11 25/64" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve



### Linden®
***Single Handle Pull-Out Kitchen Faucet***

| Model | Flow |
|---|---|
| 4153-DST | 1.5 gpm |
| 4153-AR-DST | 1.5 gpm |
| 4153-RB-DST | 1.5 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 7/8" long, 12 5/16" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- Multi-Flow™ offers 1.5 and 2.2 gpm settings



### Linden®
***Single Handle Pull-Out Kitchen Faucet***

| Model | Flow |
|---|---|
| 4353-DST | 1.5 gpm |
| 4353-AR-DST | 1.5 gpm |
| 4353-RB-DST | 1.5 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 57/64" long, 11 3/8" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- Multi-Flow™ offers 1.5 and 2.2 gpm settings



### Collins®
***Single Handle Pull-Out Kitchen Faucet***

| Model | Flow |
|---|---|
| 4140-DST | 1.8 gpm |
| 4140-AR-DST | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9" long, 10 3/8" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- MagnaTite® docking



### Foundations®
***Single Handle Pull-Out Kitchen Faucet***

| Model | Flow |
|---|---|
| B4310LF | 1.8 gpm |
| B4310LF-SS | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 8 3/4" long, 10" high
- Red/blue indicator
- 2 1/2" max. deck thickness
- 1/2" IPS connection



**See page 3 for icon definitions.**



**Almari™**
***Single Handle Pull-Out Kitchen Faucet***

| Model | Flow |
|---|---|
| 16943-DST | 1.8 gpm |
| 16943-BL-DST | 1.8 gpm |
| 16943-CZ-DST | 1.8 gpm |
| 16943-SS-DST | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 1/2" long, 11 1/2" high
- Hot/Cold Indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- MagnaTite® docking



**Daneri™**
***Single Handle Pull-Out Kitchen Faucet***

| Model | Flow |
|---|---|
| 16879-DST | 1.8 gpm |
| 16879-BL-DST | 1.8 gpm |
| 16879-CZ-DST | 1.8 gpm |
| 16879-SS-DST | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 1/2" long, 11 1/2" high
- Hot/Cold Indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- MagnaTite® docking

**See page 3 for icon definitions.**



**Classic**
***Single Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| 100-DST | 1.8 gpm |
| 100-SS-DST | 1.8 gpm |

- 3-hole 8" installation
- 8 11/16" long, 8 3/8" high
- Red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve



**Classic**
***Single Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| 101-DST | 1.8 gpm |

- 1-hole installation
- 8 11/16" long, 8 3/8" high
- Red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve



**Classic**
***Single Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| 400LF-WF | 1.8 gpm |

- 4-hole 6" or 8" installation
- 8" long, 7 13/16" high
- 1" max. deck thickness; RP30393 adds 1" to max. deck thickness
- 3/8" O.D. inlets or WF = 1/2" IPS
- Matching finish spray



**Classic**
***Single Handle Kitchen Faucet with Integral Spray***

| Model | Flow |
|---|---|
| 300LF-WF | 1.8 gpm |

- 3-hole 8" installation
- 8" long, 7 13/16" high
- 1" max. deck thickness; no thick deck kit available
- 3/8" O.D. inlets or WF = 1/2" IPS
- Matching finish spray



**Classic**
***Single Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| 420LF | 1.8 gpm |

- 4-hole 8" installation
- 8" long, 7 1/2" high
- 5/8" max. deck thickness; no thick deck kit available
- 1/2" IPS connection
- Matching finish spray



**Trinsic®**
***Single Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| 1159LF | 1.8 gpm |
| 1159LF-AR | 1.8 gpm |

- 1 or 3-hole 8" installation; for 3-hole, order RP75614 escutcheon
- 8 1/4" long, 12 5/8" high
- Red/blue indicator
- 1 7/8" max. deck thickness



**Linden®**
***Single Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| 4453-DST | 1.8 gpm |
| 4453-AR-DST | 1.8 gpm |
| 4453-RB-DST | 1.8 gpm |

- 2 or 4-hole 8" installation (optional escutcheon included)
- 9 13/16" long, 11 3/8" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- Matching finish spray



See page 3 for icon definitions.



**Linden®**
***Single Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| 1353-DST | 1.8 gpm |
| 1353-AR-DST | 1.8 gpm |
| 1353-RB-DST | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9 13/16" long, 11 3/8" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve



**Classic**
***Single Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| 400-DST | 1.8 gpm |
| 400-SS-DST | 1.8 gpm |

- 4-hole 8" installation
- 8 11/16" long, 8 3/8" high
- Red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Matching finish spray
- DIAMOND™ Valve



**Classic**
***Single Handle Kitchen Faucet with Integral Spray***

| Model | Flow |
|---|---|
| 300-DST | 1.8 gpm |

- 3-hole 8" installation
- 8 11/16" long, 8 3/8" high
- Red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Matching finish spray
- DIAMOND™ Valve



**Classic**
***Single Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| 175-DST | 1.8 gpm |

- 2-hole installation
- 8 11/16" long, 8 3/8" high
- Red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Matching finish spray
- DIAMOND™ Valve



**Classic**
***Single Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| 120LF | 1.8 gpm |

- 3-hole 8" installation
- 8" long, 7 1/2" high
- 5/8" max. deck thickness; no thick deck kit available
- 1/2" IPS connection



**Classic**
***Single Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| 100LF-WF | 1.8 gpm |

- 3-hole 8" installation
- 8" long, 7 3/16" high
- 1" max. deck thickness RP30393 adds 1" to max.
- Straight, staggered supply tubes



**Classic**
***Single Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| 101LF-WF | 1.8 gpm |

- 1-hole installation
- 8" long, 7 13/16" high
- 1 9/16" max. deck thickness
- Straight, staggered supply tubes
- 3/8" O.D. inlets or WF = 1/2" IPS

**See page 3 for icon definitions.**



**Collins®**
***Single Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| 440-DST | 1.8 gpm |
| 440-SS-DST | 1.8 gpm |
| 440-WH-DST | 1.8 gpm |

- 3 or 4-hole 8" installation
- 9 3/16" long, 8 3/4" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- Matching finish spray



**Collins®**
***Single Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| 441-DST | 1.8 gpm |
| 441-SS-DST | 1.8 gpm |

- 1 or 2-hole installation
- 9 3/16" long, 8 21/64" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- Matching finish spray



**Collins®**
***Single Handle Kitchen Faucet with Integral Spray***

| Model | Flow |
|---|---|
| 340-DST | 1.8 gpm |

- 3-hole 8" installation
- 9 3/16" long, 8 3/4" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- Matching finish spray



**Collins®**
***Single Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| 140-DST | 1.8 gpm |
| 140-WE-DST | 1.5 gpm |

- 3-hole 8" installation
- 9 3/16" long, 8 3/4" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve



**Collins®**
***Single Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| 141-DST | 1.8 gpm |
| 141-SS-DST | 1.8 gpm |

- 1-hole installation
- 9 3/16" long, 8 21/64" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve



**Foundations®**
***Single Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| B4410LF | 1.8 gpm |
| B4410LF-SS | 1.8 gpm |

- 4-hole 8" installation
- 9 1/2" long, 8 3/8" high
- Hot/cold indicator
- 1 3/8" max. deck thickness
- 1/2" IPS connection
- Matching finish spray



See page 3 for icon definitions.



### Foundations®
***Single Handle Kitchen Faucet with Integral Spray***

| Model | Flow |
|---|---|
| B3310LF | 1.8 gpm |
| B3310LF-SS | 1.8 gpm |

- 3-hole 8" installation
- 9 1/2" long, 8 3/8" high
- Hot/cold indicator
- 1 3/8" max. deck thickness
- 1/2" IPS connection
- Matching finish spray



### Foundations®
***Single Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| B1310LF | 1.8 gpm |
| B1310LF-SS | 1.8 gpm |

- 3-hole 8" installation
- 9 1/2" long, 8 3/8" high
- Hot/cold indicator
- 1 3/8" max. deck thickness
- 1/2" IPS connection

**See page 3 for icon definitions.**

NEW!



### Broderick®
***Two Handle Bridge Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 2390L-DST | 1.8 gpm |
| 2390L-AR-DST | 1.8 gpm |
| 2390L-BL-DST | 1.8 gpm |
| 2390L-CZ-DST | 1.8 gpm |
| 2390L-KS-DST | 1.8 gpm |
| 2390L-RB-DST | 1.8 gpm |

**New Polished Nickel Finish Available Q4 2025**

**Features ShieldSpray® Technology**

- 3 hole installation
- 9 5/8" long, 15 7/8" high
- Hot/cold indicators
- 3" max. deck thickness
- 30" min. InnoFlex® supply lines
- 3/8" compression fittings
- ShieldSpray® Technology powers off the mess without making a mess
- DIAMOND™ Valve
- MagnaTite® docking



### Renaldi™
***Two Handle Bridge Pull-Down Kitchen Faucet***

| Model | Flow |
|---|---|
| 2384L-PR-DST | 1.8 gpm |
| 2384L-AR-PR-DST | 1.8 gpm |
| 2384L-BL-DST | 1.8 gpm |
| 2384L-CZ-PR-DST | 1.8 gpm |
| 2384L-PN-PR-DST | 1.8 gpm |
| 2384L-RB-DST | 1.8 gpm |

**Features ProClean™ Spray**

- 3 hole installation
- 9 5/16" long, 16" high
- 3" max. deck thickness
- 32" min InnoFlex® supply lines
- 3/8" compression fittings
- Features ProClean™ Kitchen Spray Wand to provide a powerful, wide fan spray for quick and complete cleaning
- DIAMOND™ Valve
- MagnaTite® docking



### Cassidy®
***Two Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| 2497LF | 1.8 gpm |
| 2497LF-AR | 1.8 gpm |
| 2497LF-CZ | 1.8 gpm |
| 2497LF-PN | 1.8 gpm |
| 2497LF-RB | 1.8 gpm |

- 3 or 4-hole 8" installation
- 8 21/32" long, 13 15/32" high
- 1 3/4" max. deck thickness; no thick deck kit available
- 1/2" IPS connection
- Matching finish spray
- Order RP52216 for 1.5 gpm aerator insert



### Classic
***Two Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| 2400LF | 1.8 gpm |

- 4-hole 8" installation
- 9" long, 5 7/16" high
- 7/8" max. deck thickness; no thick deck kit available
- 1/2" IPS connection
- White spray



### Classic
***Two Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| 2402LF | 1.8 gpm |

- 4-hole 8" installation
- 9" long, 5 7/16" high
- 7/8" max. deck thickness; no thick deck kit available
- 1/2" IPS connection
- White spray



### Classic
***Two Handle Kitchen Faucet***

| Model | Flow |
|---|---|
| 2100LF | 1.8 gpm |

- 3-hole 8" installation
- 9" long, 5 7/16" high
- 7/8" max. deck thickness; no thick deck kit available
- 1/2" IPS connection



### Foundations®
***Two Handle Kitchen Faucet with Spray***

| Model | Flow |
|---|---|
| B2410LF | 1.8 gpm |

- 4-hole 8" installation
- 9 1/4" long, 6 7/16" high
- Hot/cold indicators
- 1 1/8" max. deck thickness
- 1/2" IPS connection
- White spray



See page 3 for icon definitions.



### Classic
***Two Handle Kitchen Faucet***

| Model | Flow | Price | Finish |
|---|---|---|---|
| 2102LF | 1.8 gpm | 139.35 | Chrome |

- 3-hole 8" installation
- 9" long, 5 7/16" high
- Hot/cold indicators
- 7/8" max. deck thickness; no thick deck kit available
- 1/2" IPS connection



### Foundations®
***Two Handle Kitchen Faucet***

| Model | Flow | Price | Finish |
|---|---|---|---|
| B2310LF | 1.8 gpm | 131.90 | Chrome |

- 3-hole 8" installation
- 9 1/4" long, 6 7/16" high
- 1 1/8" max. deck thickness
- 1/2" IPS connection
- Order RP19754 for 1.5 gpm aerator

**See page 3 for icon definitions.**

NEW!



## Trinsic®
### *Single Handle Pull-Down Bar / Prep Faucet*

FP

| Model | Flow |
|---|---|
| 9959TL-DST | 1.8 gpm |
| 9959TL-AR-DST | 1.8 gpm |
| 9959TL-BL-DST | 1.8 gpm |
| 9959TL-CZ-DST | 1.8 gpm |
| 9959TL-KS-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP64070 escutcheon
- 6 1/2" long, 13" high
- Finished red/blue indicator
- Spout swivels 360°
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

NEW!



## Broderick®
### *Single Handle Pull-Down Bar / Prep Faucet*

TE FP

| Model | Flow |
|---|---|
| 9990TL-DST | 1.8 gpm |
| 9990TL-AR-DST | 1.8 gpm |
| 9990TL-BL-DST | 1.8 gpm |
| 9990TL-CZ-DST | 1.8 gpm |
| 9990TL-KS-DST | 1.8 gpm |
| 9990TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP100845
- 6 5/8" long, 15 1/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

NEW!



## Cassidy®
### *Single Handle Pull-Down Bar / Prep Faucet*

FP

| Model | Flow |
|---|---|
| 9997TL-PR-DST | 1.8 gpm |
| 9997TL-AR-PR-DST | 1.8 gpm |
| 9997TL-CZ-PR-DST | 1.8 gpm |
| 9997TL-PN-PR-DST | 1.8 gpm |
| 9997TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

- 1 or 3-hole 8" installation, for 3 hole order RP71545
- 6 3/8" long, 14 9/16" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

NEW!



## Stryke®
### *Single Handle Pull-Down Bar / Prep Faucet*

FP

| Model | Flow |
|---|---|
| 9976TL-PR-DST | 1.8 gpm |
| 9976TL-AR-PR-DST | 1.8 gpm |
| 9976TL-BL-DST | 1.8 gpm |
| 9976TL-CZ-PR-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Matte Black / Lumicoat® Champagne Bronze™ Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP100190
- 6 9/16" long, 16 1/8" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings



See page 3 for icon definitions.

NEW!



### Emmeline®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9982TL-PR-DST | 1.8 gpm |
| 9982TL-AR-PR-DST | 1.8 gpm |
| 9982TL-BL-DST | 1.8 gpm |
| 9982TL-CZ-PR-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Lumicoat® Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 6 3/4" long, 14 3/4" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings



### Renaldi™
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9984TL-PR-DST | 1.8 gpm |
| 9984TL-AR-PR-DST | 1.8 gpm |
| 9984TL-BL-DST | 1.8 gpm |
| 9984TL-CZ-PR-DST | 1.8 gpm |
| 9984TL-PN-PR-DST | 1.8 gpm |
| 9984TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

- 1 or 3-hole 8" installation, for 3-hole order RP100845
- 6 5/8" long, 15" high
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 C
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- PR - Lumicoat™ finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking
- Toggle Between Touchless and Touch2O® only settings

NEW!



### Monrovia®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9991TL-PR-DST | 1.8 gpm |
| 9991TL-AR-PR-DST | 1.8 gpm |
| 9991TL-BL-DST | 1.8 gpm |
| 9991TL-CZ-PR-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

**New Matte Black / Lumicoat® Champagne Bronze™ Finish Available Q4 2025**

- 1 or 3-hole 8" installation, for 3 hole order RP47274
- 6 5/8" long, 16 5/8" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings



### Leland®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9678TL-DST | 1.8 gpm |
| 9678TL-AR-DST | 1.8 gpm |
| 9678TL-BL-DST | 1.8 gpm |
| 9678TL-CZ-DST | 1.8 gpm |
| 9678TL-RB-DST | 1.8 gpm |
| 9678TL-SP-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

- 1 or 3-hole 8" installation, for 3 hole order RP47274 escutcheon
- 6 3/4" long, 14 1/2" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water teamp
- 3/8" compression fittings
- SP - SpotShield® finish resists spots, prints and stains; also includes antimicrobial protection of the finish
- DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

**See page 3 for icon definitions.**



### Coranto®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9979TL-DST | 1.8 gpm |
| 9979TL-AR-DST | 1.8 gpm |
| 9979TL-BL-DST | 1.8 gpm |
| 9979TL-CZ-DST | 1.8 gpm |
| 9979TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

- 1 or 3-hole 8" installation, for 3 hole order RP47274 escutcheon
- 6 7/8" long, 14 7/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings

NEW!



### Essa®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9913TL-DST | 1.8 gpm |
| 9913TL-AR-DST | 1.8 gpm |
| 9913TL-BL-DST | 1.8 gpm |
| 9913TL-CZ-DST | 1.8 gpm |
| 9913TL-RB-DST | 1.8 gpm |

TOUCH2O® WITH TOUCHLESS™ TECHNOLOGY

- 1 or 3-hole 8" installation (optional escutcheon included)
- 6 5/8" long, 15" high
- Red/Blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- MagnaTite® docking
- Toggle between Touchless and Touch2O® only settings



### Cassidy®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9997T-PR-DST | 1.8 gpm |
| 9997T-AR-PR-DST | 1.8 gpm |
| 9997T-CZ-PR-DST | 1.8 gpm |
| 9997T-PN-PR-DST | 1.8 gpm |
| 9997T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation, for 3-hole, order RP71545 escutcheon
- 6 3/8" long 14 9/16" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- 3/8" compression fittings
- TempSense® light indicates water temp.
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



### Broderick®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9990T-DST | 1.8 gpm |
| 9990T-AR-DST | 1.8 gpm |
| 9990T-BL-DST | 1.8 gpm |
| 9990T-CZ-DST | 1.8 gpm |
| 9990T-KS-DST | 1.8 gpm |
| 9990T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 6 5/8" long, 15 1/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



### Trinsic®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9959T-DST | 1.8 gpm |
| 9959T-AR-DST | 1.8 gpm |
| 9959T-BL-DST | 1.8 gpm |
| 9959T-CZ-DST | 1.8 gpm |
| 9959T-KS-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP64070 escutcheon
- 6 1/2" long 14" high
- Red/blue indicators
- Spout swivels 360°
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

Bar/Prep/Specialty

See page 3 for icon definitions.



### Stryke®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9976T-PR-DST | 1.8 gpm |
| 9976T-AR-PR-DST | 1.8 gpm |
| 9976T-BL-DST | 1.8 gpm |
| 9976T-CZ-PR-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP100190 escutcheon
- 6 9/16" long, 16 1/8"
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- 3/8" compression fittings
- TempSense® light indicates water temp.
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



### Emmeline®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9982T-PR-DST | 1.8 gpm |
| 9982T-AR-PR-DST | 1.8 gpm |
| 9982T-BL-DST | 1.8 gpm |
| 9982T-CZ-PR-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation, for 3-hole, order RP47274 escutcheon
- 6 3/4" long, 14 3/4" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- 3/8" compression fittings
- TempSense® light indicates water temp.
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



### Monrovia®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9991T-PR-DST | 1.8 gpm |
| 9991T-AR-PR-DST | 1.8 gpm |
| 9991T-BL-DST | 1.8 gpm |
| 9991T-CZ-PR-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP47274
- 6 5/8" long, 16 5/8" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- Battery operated - 6 (AA) or 6 (C)
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- TempSense® light indicates water temp.
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking



### Leland®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9678T-DST | 1.8 gpm |
| 9678T-AR-DST | 1.8 gpm |
| 9678T-BL-DST | 1.8 gpm |
| 9678T-CZ-DST | 1.8 gpm |
| 9678T-RB-DST | 1.8 gpm |
| 9678T-SP-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP47274 escutcheon
- 6 3/4" long, 14 1/2" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- SP - SpotShield® finish resists spots, prints and stains; also includes antimicrobial protection of the finish
- DIAMOND™ Valve
- MagnaTite® docking



### Coranto®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9979T-DST | 1.8 gpm |
| 9979T-AR-DST | 1.8 gpm |
| 9979T-BL-DST | 1.8 gpm |
| 9979T-CZ-DST | 1.8 gpm |
| 9979T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation, for 3-hole, order RP47274 escutcheon
- 6 7/8" long, 14 7/8" high
- Red/blue indicators
- High-arc pull-down swivels 360°
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- Battery operated - 6 (AA) or 6 (C)
- 3/8" compression fittings
- TempSense® light indicates water temp.
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

**See page 3 for icon definitions.**



### Essa®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9913T-DST | 1.8 gpm |
| 9913T-AR-DST | 1.8 gpm |
| 9913T-BL-DST | 1.8 gpm |
| 9913T-CZ-DST | 1.8 gpm |
| 9913T-RB-DST | 1.8 gpm |

TOUCH2O® TECHNOLOGY

- 1 or 3-hole 8" installation; for 3-hole, order RP47274 escutcheon
- 6 5/8" long, 15" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- Battery operated - 6 (AA) or 6 (C)
- TempSense® light indicates water temp.
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

---

NEW!



### Broderick®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9990-DST | 1.8 gpm |
| 9990-AR-DST | 1.8 gpm |
| 9990-BL-DST | 1.8 gpm |
| 9990-CZ-DST | 1.8 gpm |
| 9990-KS-DST | 1.8 gpm |
| 9990-RB-DST | 1.8 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP100845 escutcheon
- 6 5/8" long, 14 5/8" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

---



### Cassidy®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9997-PR-DST | 1.8 gpm |
| 9997-AR-PR-DST | 1.8 gpm |
| 9997-CZ-PR-DST | 1.8 gpm |
| 9997-PN-PR-DST | 1.8 gpm |
| 9997-RB-DST | 1.8 gpm |

- 1 or 3-hole 8" installation, for 3-hole, order RP71545 escutcheon
- 6 3/8" long, 14 1/2" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines
- 3/8" compression fittings
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

---

NEW!



### Stryke®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9976-PR-DST | 1.8 gpm |
| 9976-AR-PR-DST | 1.8 gpm |
| 9976-BL-DST | 1.8 gpm |
| 9976-CZ-PR-DST | 1.8 gpm |

**New Matte Black / Lumicoat® Champagne Bronze™ Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP100190 escutcheon
- 6 9/16" long, 16 1/8"
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- Euro-Motion DIAMOND™ Valve
- MagnaTite® docking

---

NEW!



### Trinsic®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9959-DST | 1.8 gpm |
| 9959-AR-DST | 1.8 gpm |
| 9959-BL-DST | 1.8 gpm |
| 9959-CZ-DST | 1.8 gpm |
| 9959-KS-DST | 1.8 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP64070 escutcheon
- 6 1/2" long, 13" high
- Red/blue indicators
- Spout swivels 360°
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



**See page 3 for icon definitions.**

NEW!



### Trinsic® *Limited Swivel Single Handle Pull-Down Bar / Prep Faucet*

| Model | Flow |
|---|---|
| 9959-LS-DST | 1.8 gpm |
| 9959-ARLS-DST | 1.8 gpm |
| 9959-BLLS-DST | 1.8 gpm |
| 9959-CZLS-DST | 1.8 gpm |
| 9959-KSLS-DST | 1.8 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP64070 escutcheon
- 6 1/2" long, 13" high
- Red/blue indicators
- Spout swivels 140°
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



### Emmeline® *Single Handle Pull-Down Bar / Prep Faucet*

| Model | Flow |
|---|---|
| 9982-PR-DST | 1.8 gpm |
| 9982-AR-PR-DST | 1.8 gpm |
| 9982-BL-DST | 1.8 gpm |
| 9982-CZ-PR-DST | 1.8 gpm |

**New Lumicoat® Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 8" installation (optional escutcheon included)
- 6 3/4" long, 14 3/4" high
- Hot/cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines
- 3/8" compression fittings
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



### Monrovia® *Single Handle Pull-Down Bar / Prep Faucet*

| Model | Flow |
|---|---|
| 9991-PR-DST | 1.8 gpm |
| 9991-AR-PR-DST | 1.8 gpm |
| 9991-BL-DST | 1.8 gpm |
| 9991-CZ-PR-DST | 1.8 gpm |

**New Matte Black / Lumicoat® Champagne Bronze™ Finish Available Q4 2025**

- 1 or 3-hole 8" installation; for 3-hole, order RP47274
- 6 5/8" long, 16 1/8" high
- Hot/Cold indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- PR - Lumicoat® finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking



### Renaldi™ *Single Handle Pull-Down Bar / Prep Faucet*

| Model | Flow |
|---|---|
| 9984-PR-DST | 1.8 gpm |
| 9984-AR-PR-DST | 1.8 gpm |
| 9984-BL-DST | 1.8 gpm |
| 9984-CZ-PR-DST | 1.8 gpm |
| 9984-PN-PR-DST | 1.8 gpm |
| 9984-RB-DST | 1.8 gpm |

**Features ProClean™ Spray**

- 1 or 3-hole 8" installation order RP100845
- 6 5/8" long, 15" high
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euromotion DIAMOND™ Valve
- PR - Lumicoat™ finishes, guaranteed to resist mineral buildup and hard water stains
- MagnaTite® docking



### Leland® *Single Handle Pull-Down Bar / Prep Faucet*

| Model | Flow |
|---|---|
| 9978-DST | 1.8 gpm |
| 9978-AR-DST | 1.8 gpm |
| 9978-BL-DST | 1.8 gpm |
| 9978-CZ-DST | 1.8 gpm |
| 9978-RB-DST | 1.8 gpm |

- 2-hole 4" installation
- 6 11/16" long, 14" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve
- MagnaTite® docking



### Leland® *Single Handle Pull-Down Bar / Prep Faucet*

| Model | Flow |
|---|---|
| 9678-DST | 1.8 gpm |
| 9678-AR-DST | 1.8 gpm |
| 9678-BL-DST | 1.8 gpm |
| 9678-CZ-DST | 1.8 gpm |
| 9678-RB-DST | 1.8 gpm |
| 9678-SP-DST | 1.8 gpm |

- 1 or 3-hole 8" installation; for 3-hole, order RP47274 escutcheon
- 6 3/4" long, 14 1/2" high
- Finished red/blue indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- SP - SpotShield® finish resists spots, prints and stains; also includes antimicrobial protection of the finish
- DIAMOND™ Valve
- MagnaTite® docking

**See page 3 for icon definitions.**



### Coranto®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9979-DST | 1.8 gpm |
| 9979-AR-DST | 1.8 gpm |
| 9979-BL-DST | 1.8 gpm |
| 9979-CZ-DST | 1.8 gpm |
| 9979-RB-DST | 1.8 gpm |

- 1 or 3-hole 8" installation, for 3-hole, order RP47274 escutcheon
- 6 7/8" long, 14 7/8" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" minimum InnoFlex® supply lines included
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking



### Essa®
***Single Handle Pull-Down Bar / Prep Faucet***

| Model | Flow |
|---|---|
| 9913-DST | 1.8 gpm |
| 9913-AR-DST | 1.8 gpm |
| 9913-BL-DST | 1.8 gpm |
| 9913-CZ-DST | 1.8 gpm |
| 9913-RB-DST | 1.8 gpm |

- 1 or 3-hole 8" installation; for 3-hole, order RP70714 escutcheon
- 6 5/8" long, 14 1/2" high
- Red/blue indicators
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- Euro-motion DIAMOND™ Valve
- MagnaTite® docking

NEW!



### Broderick®
***Single Handle Bar Faucet***

| Model | Flow |
|---|---|
| 1990LFC | 1.5 gpm |
| 1990LFC-AR | 1.5 gpm |
| 1990LFC-BL | 1.5 gpm |
| 1990LFC-CZ | 1.5 gpm |
| 1990LFC-KS | 1.5 gpm |
| 1990LFC-RB | 1.5 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3-hole 4" installation; for 3-hole, order RP100844 escutcheon
- 7 1/16" long, 12 1/4" high
- Hot/Cold Indicators
- 2 1/2" max. deck thickness
- Ceramic disc cartridge



### Cassidy®
***Single Handle Bar Faucet***

| Model | Flow |
|---|---|
| 1997LF | 1.5 gpm |
| 1997LF-AR | 1.5 gpm |
| 1997LF-CZ | 1.5 gpm |
| 1997LF-PN | 1.5 gpm |
| 1997LF-RB | 1.5 gpm |

- 1 or 3-hole 4" installation; for 3-hole, order RP72711 escutcheon
- 5 15/16" long, 8 3/4" high
- Hot/cold indicator
- 2 1/2" max. deck thickness
- 3/8" staggered copper supply lines with 1/2" fittings
- Euro-motion valve

NEW!



### Contemporary
***Single Handle Bar Faucet***

| Model | Flow |
|---|---|
| 1959LF | 1.5 gpm |
| 1959LF-AR | 1.5 gpm |
| 1959LF-BL | 1.5 gpm |
| 1959LF-CZ | 1.5 gpm |
| 1959LF-KS | 1.5 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1 or 3 hole 4" installation; for 3-hole, order RP77702 escutcheon
- 5 15/16" long, 11 1/2" high
- Hot/cold indicator
- 2 1/2" max. deck thickness
- 3/8" staggered copper supply lines with 1/2" fittings
- Euro-motion valve
- Limited swivel spout: 120°



### Transitional
***Single Handle Bar Faucet***

| Model | Flow |
|---|---|
| 1953LF | 1.5 gpm |
| 1953LF-AR | 1.5 gpm |
| 1953LF-CZ | 1.5 gpm |

- 1 or 3 hole 4" installation; for 3-hole, order RP77702 escutcheon
- 5 3/8" long, 12 5/16" high
- Hot/cold indicator
- 2 1/2" max. deck thickness
- 3/8" staggered copper supply lines with 1/2" fittings
- Euro-motion valve



See page 3 for icon definitions.



### Classic
***Single Handle Bar Faucet***

| Model | Flow |
|---|---|
| 1903-DST | 1.5 gpm |
| 1903-SS-DST | 1.5 gpm |

- 2-hole 4" installation
- 5" long, 10" high
- High arc spout swivels 180°
- Finished hot/cold indicator
- 2 1/2" max. deck thickness
- 32" min. InnoFlex® supply lines
- 3/8" compression fittings
- DIAMOND™ Valve



### Classic
***Two Handle Bar Faucet***

| Model | Flow |
|---|---|
| 2171LF | 1.5 gpm |

- 2 or 3-hole 4" installation
- 4 1/8" long, 11" high
- 1" max. deck thickness; no thick deck kit available
- 1/2" IPS connection



### Foundations®
***Two Handle Bar Faucet***

| Model | Flow |
|---|---|
| B28910LF | 1.8 gpm |

- 2 or 3-hole 4" installation
- 5" long, 11" high
- 1" max. deck thickness; no thick deck kit available
- 1/2" IPS connection



### Foundations®
***Two Handle Bar Faucet***

| Model | Flow |
|---|---|
| B28911LF | 1.8 gpm |
| B28911LF-SS | 1.8 gpm |

- 2 or 3-hole 4" installation
- 5 1/16" long, 11 7/16" high
- 1" max. deck thickness; no thick deck kit available
- 1/2" IPS connection

**See page 3 for icon definitions.**

NEW!



### *Contemporary Round Beverage Faucet*

| Model | Flow |
|---|---|
| 1930-DST | 1.5 gpm |
| 1930-AR-DST | 1.5 gpm |
| 1930-BL-DST | 1.5 gpm |
| 1930-CZ-DST | 1.5 gpm |
| 1930-KS-DST | 1.5 gpm |
| 1930-RB-DST | 1.5 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1-hole installation
- 5 1/16" long, 9 1/2" high
- Cold water only
- 3/8" compression fittings
- 3" max. deck thickness
- 32" min. InnoFlex® supply line
- Works with RO systems, filtered water systems, chillers, or as a cold water tap
- Works with Delta Reverse Osmosis System DWQ1001012
- DIAMOND™ Valve



### *Traditional Beverage Faucet*

| Model | Flow |
|---|---|
| 1960-DST | 1.5 gpm |
| 1960-AR-DST | 1.5 gpm |
| 1960-BL-DST | 1.5 gpm |
| 1960-CZ-DST | 1.5 gpm |
| 1960-KS-DST | 1.5 gpm |
| 1960-PN-DST | 1.5 gpm |
| 1960-RB-DST | 1.5 gpm |

- 1-hole installation
- 5 1/16" long, 9 1/2" high
- Cold water only
- 3/8" compression fittings
- 3" max. deck thickness
- 32" min. InnoFlex® supply line
- Works with RO systems, filtered water systems, chillers, or as a cold water tap
- Works with Delta Reverse Osmosis System DWQ1001012
- DIAMOND™ Valve



### *Contemporary Square Beverage Faucet*

| Model | Flow |
|---|---|
| 1940-DST | 1.5 gpm |
| 1940-AR-DST | 1.5 gpm |
| 1940-KS-DST | 1.5 gpm |
| 1940-PN-DST | 1.5 gpm |
| 1940-RB-DST | 1.5 gpm |

- 1-hole installation
- 5 1/16" long, 9 1/2" high
- Cold water only
- 3/8" compression fittings
- 3" max. deck thickness
- 32" min. InnoFlex® supply line
- Works with RO systems, filtered water systems, chillers, or as a cold water tap
- Works with Delta Reverse Osmosis System DWQ1001012
- DIAMOND™ Valve



### *Transitional Beverage Faucet*

| Model | Flow |
|---|---|
| 1920-DST | 1.5 gpm |
| 1920-AR-DST | 1.5 gpm |
| 1920-BL-DST | 1.5 gpm |
| 1920-CZ-DST | 1.5 gpm |
| 1920-KS-DST | 1.5 gpm |
| 1920-RB-DST | 1.5 gpm |

- 1-hole installation
- 5 1/16" long, 9 1/2" high
- Cold water only
- 3/8" compression fittings
- 3" max. deck thickness
- 32" min. InnoFlex® supply line
- Works with RO systems, filtered water systems, chillers, or as a cold water tap
- Works with Delta Reverse Osmosis System DWQ1001012
- DIAMOND™ Valve

**See page 3 for icon definitions.**

NEW!



### *Contemporary Round Instant Hot Faucet*

| Model | Flow |
|---|---|
| 1930LF-H | 1.5 gpm |
| 1930LF-H-AR | 1.5 gpm |
| 1930LF-H-BL | 1.5 gpm |
| 1930LF-H-CZ | 1.5 gpm |
| 1930LF-H-KS | 1.5 gpm |
| 1930LF-H-RB | 1.5 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1-hole installation
- 5" long, 9 7/16" high
- Delivers near boiling water on demand
- Self-closing spring loaded handle
- 3/8" compression fittings 3" max. deck thickness
- 32" min. InnoFlex® supply line
- Tank and filter required to be purchased separately and not available thru Delta Faucet. Recommended tanks include InSinkErator® HWT-300-F2000S, HWT300-F3000S or HWT300 InSinkerator tank models



### *Traditional Instant Hot Faucet*

| Model | Flow |
|---|---|
| 1960LF-H | 1.5 gpm |
| 1960LF-H-AR | 1.5 gpm |
| 1960LF-H-BL | 1.5 gpm |
| 1960LF-H-CZ | 1.5 gpm |
| 1960LF-H-KS | 1.5 gpm |
| 1960LF-H-PN | 1.5 gpm |
| 1960LF-H-RB | 1.5 gpm |

- 1-hole installation
- 5 1/16" long, 9 1/2" high
- Delivers near boiling water on demand
- Self-closing spring loaded handle
- 3/8" compression fittings
- 3" max. deck thickness
- 32" min. InnoFlex® supply line
- Tank and filter required to be purchased separately and not available thru Delta Faucet. Recommended tanks include InSinkErator® HWT-300-F2000S, HWT300-F3000S or HWT300 InSinkerator tank models



### *Contemporary Square Instant Hot Faucet*

| Model | Flow |
|---|---|
| 1940LF-H | 1.5 gpm |
| 1940LF-H-AR | 1.5 gpm |
| 1940LF-H-KS | 1.5 gpm |
| 1940LF-H-PN | 1.5 gpm |
| 1940LF-H-RB | 1.5 gpm |

- 1-hole installation
- 5 1/16" long, 9 1/2" high
- Delivers near boiling water on demand
- Self-closing spring loaded handle
- 3/8" compression fittings
- 3" max. deck thickness
- 32" min. InnoFlex® supply line
- Tank and filter required to be purchased separately and not available thru Delta Faucet. Recommended tanks include InSinkErator® HWT-300-F2000S, HWT300-F3000S or HWT300 InSinkerator tank models

See page 3 for icon definitions.

NEW!



### Broderick®
### *Wall Mount Pot Filler*

| Model | Flow |
|---|---|
| 1190LFL | 4.0 gpm |
| 1190LFL-AR | 4.0 gpm |
| 1190LFL-BL | 4.0 gpm |
| 1190LFL-CZ | 4.0 gpm |
| 1190LFL-KS | 4.0 gpm |
| 1190LFL-RB | 4.0 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1-hole installation
- 24" long, 9 1/4" high
- Two handle wall mount
- Cold water only
- Dual shut-off and swing joints
- 24" reach
- 1/2" IPS inlets

NEW!



### *Contemporary Wall Mount Pot Filler*

| Model | Flow |
|---|---|
| 1165LF | 4.0 gpm |
| 1165LF-AR | 4.0 gpm |
| 1165LF-BL | 4.0 gpm |
| 1165LF-CZ | 4.0 gpm |
| 1165LF-KS | 4.0 gpm |
| 1165LF-SS | 4.0 gpm |

**New Polished Nickel Finish Available Q4 2025**

- 1-hole installation
- 21 9/16" long, 8 1/8" high
- Two handle wall mount
- Cold water only
- Dual shut-off and swing joints
- 24" reach
- 1/2" IPS inlets



### *Traditional Wall Mount Pot Filler*

| Model | Flow |
|---|---|
| 1177LF | 4.0 gpm |
| 1177LF-AR | 4.0 gpm |
| 1177LF-CZ | 4.0 gpm |
| 1177LF-PN | 4.0 gpm |
| 1177LF-RB | 4.0 gpm |
| 1177LF-SS | 4.0 gpm |

- 1-hole installation
- 23 5/8" long, 10 1/6" high
- Two handle wall mount
- Cold water only
- Dual shut-off and swing joints
- 24" reach
- 1/2" IPS inlets

**See page 3 for icon definitions.**



### *Metal Glass Rinser*

FP

- 1-hole installation
- 2 1/2" long, 1 1/8" high
- 2 1/2" max. deck thickness
- 1.2 gpm max flow rate
- 1/2" IPS shank(s)
- Supply line and T-Adapter included
- Matching finished cover included

| Model | Finish |
|---|---|
| GR250 | Chrome |
| GR250-AR | Arctic® Stainless |
| GR250-BL | Matte Black |
| GR250-CZ | Champagne Bronze™ |
| GR250-KS | Black Stainless |
| GR250-PN | Polished Nickel |
| GR250-RB | Venetian Bronze® |



### *Air Switch with Dual Outlet*

FP

- Plug-in dual outlet controller for waste disposal and one additional accessory
- Brass button and trim with polyethylene body
- Installed in 1-1/4" openings
- 6' flexible hose included
- Order RP101682 for replacement button and tubing

| Model | Finish |
|---|---|
| 72050 | Chrome |
| 72050-AR | Arctic® Stainless |
| 72050-BL | Matte Black |
| 72050-CZ | Champagne Bronze™ |
| 72050-GB | Brushed Gold |
| 72050-KS | Black Stainless |
| 72050-PN | Polished Nickel |
| 72050-RB | Venetian Bronze® |



### *Kitchen Sink Flange & Strainer*

FP

- Polypropylene drain housing
- Brass strainer and basket
- Top-mount flange installation for 3.5" sink openings
- 4 1/2" diameter brass flange
- 1 1/2" x 11 1/2" NPSM threads
- Meets ASME B1.20.3

| Model | Finish |
|---|---|
| 72010 | Chrome |
| 72010-AR | Arctic® Stainless |
| 72010-CZ | Champagne Bronze™ |
| 72010-GB | Brushed Gold |
| 72010-KS | Black Stainless |
| 72010-PN | Polished Nickel |
| 72010-SS | Brilliance® Stainless |



### *Air Gap*

FP

- Polyethylene body
- 5/8" dishwasher inlet, 7/8" outlet
- 1 5/8" diameter, 2 1/8" long brass cap

| Model | Finish |
|---|---|
| 72020 | Chrome |
| 72020-AR | Arctic® Stainless |
| 72020-BL | Matte Black |
| 72020-CZ | Champagne Bronze™ |
| 72020-GB | Brushed Gold |
| 72020-KS | Black Stainless |
| 72020-PN | Polished Nickel |
| 72020-RB | Venetian Bronze® |
| 72020-SS | Brilliance® Stainless |



### *Kitchen Disposal & Flange Stopper*

FP

- 4 1/2" diameter brass flange

| Model | Finish |
|---|---|
| 72030 | Chrome |
| 72030-AR | Arctic® Stainless |
| 72030-CZ | Champagne Bronze™ |
| 72030-GB | Brushed Gold |
| 72030-KS | Black Stainless |
| 72030-PN | Polished Nickel |
| 72030-SS | Brilliance® Stainless |

**See page 3 for icon definitions.**





**Collins®**
***Single Handle Tract-Pack Pull-Out Kitchen Faucet***

| Model | Flow |
|---|---|
| * 4140-TP-DST | 1.8 gpm |
| * 4140-ARTP-DST | 1.8 gpm |

- 1 or 3-hole 8" installation (optional escutcheon included)
- 9" long, 10 3/10" high
- Finished hot/cold indicator
- 3/8" compression fittings
- 32" min. InnoFlex® supply lines
- 2 1/2" max. deck thickness
- Restricted to case pack of 3 - priced each
- DIAMOND™ Valve

***Models noted with an * must be ordered in case quantity, priced each.**
**See page 4 for icon definitions.**

**See page 3 for icon definitions.**

AKABA

akaba.mx